

READER/PRINTERS - 105MM FICHE/JACKET

800 Microfiche Dry Reader-Printer

This is a "MICROFICHE READER" for occasional prints!



A low cost, very low volume dry silver unit for reading and that occasional print. Uses only paper, no toners, liquids or powders.

Delivers variable length, dry-silver prints. For operator convenience, a front-delivered, tabletop dry copy is available in 10 seconds. Print length may be either 8½" or 11", accommodating source or COM film economically. Exposure control compensates for wide variation in film density. A 152-meter (500-foot) roll produces up to 700 prints.

Convenient controls and ideal indexing. All controls are at operator's fingertips. Up-front convenience makes the task easy whether viewing or printing. Standby switch keeps system ready to print on demand. COM and source document index grids for popular reductions make finding information quick and easy.

Bright Images from source or COM film. 14" x 13.5" non-glare, hooded screen presents big, sharp images from both types of film. Source document image is over 100% of original size; COM film image is 88% of original. Dual lens holder accommodates any pair of lenses. Long-life, quartz halogen lamp.

Precision fiche handler. Easily and smoothly moved in any direction. Accepts fiche and jackets between self-opening glass flats for single 105mm x 148mm or 85.7mm x 187.3mm. Self-opening right side and manual-opening left side glass flats for dual 105mm x 148mm.

Typical Machine Characteristics

Microfiche Handler:

Horizontal on precision slides; glass flat supports floating lenses.

Microforms Accepted:

Single or dual 4" x 6" (105mm x 148mm), or 3⅜" x 7⅜" (85.7mm x 187.3mm) Microfiche.

Indexing: COM and Source

Document Index Grids for 24X, 42X and 48X Reduction Microfiche.

Print Process: 3M Dry Silver.

Print Time: 10 seconds; 7 seconds for successive prints.

Print Paper Format: 152-meter (500-foot) roll, 8½" or 11"

width (216mm or 279mm); 76-meter (250-foot) roll, 8½" or 11" width (216mm or 279mm).

Print Size: 8½"W x 11"L (216mm x 279mm), 8½"W x 8½"L (216mm x 216mm), 11"W x 11"L (279mm x 279mm), 11"W x 8½"L (279mm x 216mm).

Screen Size: 14" x 13.5" (356mm x 343mm).

Available Lenses: For 18X, 24X, 32X, 36X, 42X, 48X, 72X and 92X Reduction Film; dual lenses optional.

Dimensions: 20"W x 26½"D x 26"H (508mm x 673mm x 660mm).

Weight: 105 lbs. (48 kg) without packaging.

Electrical Requirements:

Domestic: 105-125 volts, 60 Hz AC, 10 amp.

International: 90-250 volts, 50/60 Hz AC, 10 amp.

Stand: Optional.

Coin Attachment: Available as an optional accessory at an additional cost.

Typical Characteristics noted herein are subject to change without prior written notice.