

## CAMERAS – 16MM ROTARY

### Kodak Mini Microfilmer

Portable, 16mm rotary microfilmer no wider than a standard office typewriter that microfilms documents up to 12" wide by any length quickly, easily, and economically, offering these features:



- Films 60 letters or 125 checks per minute.
- Three-level image marking capability is standard, making document recall and sorting faster and easier.
- The accessory footswitch adds speed and convenience to image marking.
- Eight-digit document counter helps you to track even the biggest jobs.
- High resolution and improved exposure control for multi-colored documents.
- 25:1 (nominal) reduction ratio.
- Resolution – 100:1 Lines/mm, minimum.

#### Typical Machine Characteristics

Weight: 30 lbs. (13.57 kg).

Size: 6.5"H x 15.5"W x 12.5"D (16.5cm x 39.4cm x 31.8cm).

Power: 100, 110, 120 volts ac, 50 or 60 Hz. 220 240 volts ac, 50 or 60 Hz.

### Kodak Reliant Intelligent Microfilmer 1000

This versatile 16mm rotary microfilmer offers rapid image documentation, applications flexibility, electronic indexing, and film writing for a cost-effective approach to file control for low- to medium-volume applications. It has such features as:

- High-speed operation (600 documents per minute).
- Low-cost interchangeable microfilm cassettes capable of two film thicknesses.
- Expanded image mark capability with one to three level indexing.
- Allows up to 11 indexing digits written directly on film, requiring no document imprinter.
- 23-digit keypad and a 12-digit LED display for indexing flexibility.
- Microprocessor-controlled to monitor number-writing on film and most other microfilmer operations.
- Automatic Exposure Control with capability for manual fixed exposure operation.
- Simplex-, duplex-, or duo-filming capabilities.
- Audible alarms and visual indicators of machine status.
- Built-in resettable odometer.
- Resettable document counter.



#### Typical Machine Characteristics

Weight: 175 lbs. (79 kg) 205 lbs (93 kg) shipping weight.

Size: 13 1/4"H x 27 1/2"W x 33"D (337mm x 698mm x 838mm) all with cover closed..

Power: 104-27 v, 60 Hz, or 113-27 v, 50 Hz (7 amps maximum) or 198-254 v, 50 Hz with internal wiring changes.